

 Cannula
those who take care of us

As part of your job and your passion, you care for hundreds of patients every day. Doctor, nurses and medical staff are depended upon in times of need. As a health professional you can now depend on someone as well.

HEALTHCARE PROFESSIONALS ARE AT HIGH RISK

As per WHO, among the 35 million health professionals worldwide, about 3 million receive percutaneous exposures to blood borne pathogens each year, 90% of these infections occur in developing countries.

WHENEVER YOU ARE ON DUTY, CATHY IS ALSO ON DUTY

A protection device **SPCLP**^{*} encapsulates the tip of the used needle when introducer needle is extracted from the catheter; Post Cannulation. SIPCLIP prevents accidental needle stick injury provided that general effective and safe working procedures and precautions are maintained during its use and disposal.

AUTO PROTECTION

The hassel-free and auto protection technology of CATHY I.V Cannula is desiged to provide "Involuntary Activated Safety" - an intuitive mechanism that requires no additional training of the health staff and strives to make I.V insertion and introducer needle extraction completely safe.

COMPONENTS

NEEDLE

Siliconised electrofinished, back cut bevelled stainless steel needle

Instant Flash Back Notch on 24G and 26G Cannula



NEEDLE HUB

Allows blood flash back visualisation. Thumb rest for proper grip during insertion.

CATHETER Available in VOLEX™ polyuerthane radio detectable.

LUER LOCK CAP

Closure to wing housing permits patient mobility when infusion temporarily discontinued.

BLOOD STOPPER

The stopper has fine air vent to expedite blood flash back for enabling correct cannulation.

PRODUCT RANGE

INJECTION PORT CAP

It facilitates extra medication and also prevents its back flow.

BLISTER PACKAGE

Cannula is packed in rigid blister and sealed in peel open type medical grade

Colour Code	Gauge	Catheter Ext. DiaxLength(mm)	Water flow-rate
Grey	16G	1.70 x 45	200
White	17G	1.50 x 45	140
Green	18G	1.20 x 38	105
		1.20 x 45	100
Pink	20 G	1.00 x 32	64
Blue	22G	0.80 x 25	38



Scan to Visit Product Video



Scan to Visit Product Page

